

Wiring, Printed - Component

COMPANY

BETA LAYOUT GMBH

IM AARTAL 14

AARBERGEN, Hessen 65326 Germany

E321281

Type	Cond Width		Cond Thk	SS/DSO	Area Diam	Date After	Surface Mount	Assembly Solder		Solder Limits	Oper Temp	Max Flame	Meets UL796	C T	
	mm	mm						Process	Process						°C
Multilayer printed wiring boards															
M	0.075	0.075	18 Int:35	DS	50.8	No	-	-	-	288	20	130	V-0	All	*
Multilayer printed wiring boards with an embedded RFID module, flammability only Recognition															
E	-	-	-	DS	-	No	-	-	-	288	20	-	V-0	-	-
Single layer printed wiring boards															
S	0.075	0.075	18	DS	50.8	No	-	-	-	288	20	130	V-0	All	*
Single layer printed wiring boards with an embedded RFID module, flammability only Recognition															
F	-	-	-	DS	-	No	-	-	-	288	20	-	V-0	-	-

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or tradename "BL" or file number and type designation. May be followed by a suffix to denote factory identification or flammability classification..

Last Updated on 2022-06-18

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."